
Signal Processing System for Imbedded Transparent Ultrasonic Emitter in Smartphones

Xinyu Gong, Zexi Huang, Boyu Ning, Junyu Tao, Ziyi Yuan Yincai Honors College University of Electronic Sci. and Tech, of China

Reference	_
Plan	
Procedure	
Objectives	
Goal / Scope	
Goal / Scope Backgrou <mark>nd</mark>	

Background

"Parametric End-fire Array" (Westervelt, 1960)






Fig. 1 Brief explanation on "parametric end-fire array"

1963

Westervelt

Westervelt Equation

Fundamental equation of parametric array


1965 Berktay

Berktay Equation Simple model on farfield array


1969, 1971 Zabolotskaya, Khokhlov, Kuznetsov




KZK Equation One of the most efficient models "Audio Spotlight" (Yoneyama et al., 1983)



"Audio Spotlight" (Yoneyama et al., 1983)



Kamakura pointed out three problems to solve in parctical implement (Kamakura et al., 1984):





Attenuating amplitude of ultrasound

Optimal parameters

Moffett and Mellen, 1977; Aoki et al., 1994

Distortion reduction

Kamakura et al., 1984; Kite et al., 1998

Attenuating amplitude of ultrasound

Kamakura et al., 1984

.


Propagation model of finite amplitude sound beams

Yang et al., 2005

"Transparent parametric emitter" (Hecht et al., 2005)



"Transparent parametric emitter" (Hecht et al., 2005)



"Transparent parametric emitter" (Hecht et al., 2005)










"thin, thiner, ultra thin"


thickness of marketing

Few reports have mentioned the the detailed design of signal processing system before the emitting stage.

Goal / Scope



Solid, extendible and well-performed








Fig. 2 Prototype of a signal processing system for ultrasound emitter





Design or improvement of the ultrasound emitter















[Function]

Converting analog signals into digital signals;

Adjusting the amplitude of different frequency by digital filter.



[Purpose]

Adding protection to the electric signal;

Compensating the distortion in device;

Restoring the original acoustic signal.



[Implement]

Field – programmable gate array;

System on chip.

Detecting the test signal and describe the spectrum.



Compared with the range of international standard.

Calculating parameter and design corresponding filters.


Detecting the test signal and describe the spectrum.



Detecting the test signal and describe the spectrum.



Compared with the range of international standard.



Calculating parameter and design corresponding filters.

[IIR design]OO

The most common practice is to transform H_a(s) into the desired digital G(z) transfer function


[Methods]

The Impulse Invariance Method The Bilinear Translation Method convert the digital filter specification to analog low pass prototype filter specifications


determine the analog low pass filter transfer function meeting these specifications

transform the analog filter in to the desired transfer function. Detailed 3-step


Calculating parameter and design corresponding filters.




Limit the dynamic range of the signal.




Downward Compression





Two major benefits: Free membrane protection; Audio quality improvement.





Two major benefits: Free membrane protection; Audio quality improvement.


Two common implementations: Feedback design; Feedforward design.

Adaptive, based on DSP techniques.


Different advantages and disadvantages.










Measurements at output port; Controller adjusts DRC parameters; DRC adapts to the current signal.








Measurements at output port; Controller adjusts DRC parameters; DRC adapts to the current signal.



Function

Measurements at output port in loop; Information directly sent to controller; Controller adjusts parameters of both DRCs.



Feedforward:

Instantaneous parameter adjustment; Requires duplicate DRCs.

Feedback:

Small delay;

Single DRC.

Compressor

Feedforward:


Instantaneous parameter adjustment; Requires duplicate DRCs.

Feedback:

Small delay; Single DRC.

Choice:

Performance vs. Power consumption




[Purpose]

Eliminate the sound out of people's hearing range; Eliminate audible beat signal.


[Parameter]

Passband: 11kHz;


Stopband: 20kHz (<24kHz).




[Active low-pass filter]
Steep roll-off and low noise;
Easy to be integrated;
No attenuation.



Frequency
Response
Low Pass
Filter





[Purpose]

Eliminate the sound out of people's hearing range; Eliminate audible frequencies.


[Parameter]

Passband: 200Hz(before modulation),

26kHz(after modulation);


Stopband: 20kHz(before modulation),


23kHz(after modulation).



[Active high-pass filter]
Steep roll-off and low noise;
Easy to be integrated;
No attenuation.

Frequency
Response
High Pass
Filter





[Function]

Combining the signal with ultrasonic carrier wave.

[Purpose]


Finding the optimal frequencies of carrier wave, such that the directionality of the loudspeaker is improved and the sound received by audience is clearer.



The optimum frequency of the primary wave is dependent on (Aoki et al., 1994):

The transmitter radius,
The source pressure,
The location of the observation point.







	Description of Work	Start & End Dates
Phase 1	Personnel recruitment, needs assessment, field study, materials preparation.	Apr. 1st to Apr.30th
Phase 2	(i)System Design, Prototype Building, (ii)Testing and enhancement.	(i) May. 1st to Jun. 30th (ii) Jul. 1st to Aug. 31st
Phase 3	Feedback, Productization (including miniaturization), Product Training.	Sep. 1st to Oct. 15th

Budget

	Description of Budget	Start & End Dates
Phase 1	Labor costs: \$13000 Materials preparation: \$15000	Apr. 1st to Apr.30th
Phase 2	(i) Labor costs: \$ 26000Supplies: \$ 1000(ii) Labor costs: \$ 26000Additional material: \$ 5000	(i) May. 1st to Jun. 30th (ii) Jul. 1st to Aug. 31st
Phase 3	Labor costs: \$ 26000 Productization cost: \$ 20000	Sep. 1st to Oct. 15th



Objectives

Indicators

High audio quality

Distortion less than 1%

Miniaturization

Imbeded into a smartphone (e.g. iPhone)

Low power cosumption


Power under 3w

Harsh condition resistence

Temperature range of 0~40°C

Robustness

More than 4 years.



12 months

